



36596

36596



Product details

SKU	36596
EAN 13	8712418435979
Units per product (pcs.)	1
Weight (netto) (kg)	60 kg
Length (mm)	650 mm (6.5 dm)
Width (mm)	560 mm (5.6 dm)
Height (mm)	1,165 mm (1.165 m)
Drive	Direct driven 1:1
Start	Direct
Motor type	4-poles
Motor power (hp / kW)	3.0 HP / 2.2 kW
Motor efficiency class	S3 - 75%
Cylinders	4
Stages	1
Pump speed (rpm)	1400
Air Receiver	Yes
Capacity air receiver (l)	90
Galvanized tank	No
Workload (labor/rest %)	70/30
Maximum pressure (bar)	10
Cut-in pressure (bar)	8 bar
Intake capacity (l/min)	440 L/m (2.64 kL/s)
Free air delivery (l/min)	350 L/m (2.1 kL/s)
Free air delivery (m3/h)	20.4 m³/h (5.667 dm³/s)
Noise level dB (A) (0 m)	94
Noise level dB(A) (4 m)	73

Sound volume reduction	No
Connection type	Universal
Number of couplings air connections	1
Number of reducable couplings air connections	1
Ambient temperature (°C)	5°C - 30°C
Oilfree	Yes
Voltage (V)	230 V / 50 Hz / 1 Ph
Cable length (m)	1.8 m
After cooler	No
Intercooler	No
Wheels	Yes
Filter with reducer	No

