



# 36874

36874



## Product details

Weight (netto) (kg)	25 kg
Gross weight (kg)	26 kg
Length (mm)	971 mm (9.71 dm)
Width (mm)	386 mm (3.86 dm)
Height (mm)	776 mm (7.76 dm)
SKU	36874
Drive	V-belt driven
Start	Direct
Motor type	AC
Motor efficiency class	F
Cylinders	2
Stages	1
Pump speed (rpm)	1400
Belt size	a-1168
Flywheel diameter (mm)	280 mm (2.8 dm)
Pulley diameter (mm)	90 mm (9 cm)
Air Receiver	Yes
Galvanized tank	No
Workload (labor/rest %)	30/70
Minimum working pressure (bar)	8 bar
Free air delivery (m <sup>3</sup> /h)	12.65 m <sup>3</sup> /h (3.514 dm <sup>3</sup> /s)
Free air delivery at 6 bar (l/min)	190 L/min (3.167 L/s)
Free air delivery at 7 bar (l/min)	170 L/min (2.833 L/s)
Noise level dB(A) (4 m)	71
Connection type	Universal
Main air connection (")	1/4

Number of couplings air connections	2
Number of reducable couplings air connections	1
Ambient temperature (°C)	5°C - 40°C
Oilfree	No
Oil capacity (l)	0.66
Cable length (m)	2.2 m
After cooler	Yes
Intercooler	No
Wheels	Yes
Motor power (hp / kW)	3.0 HP / 2.2 kW
Capacity air receiver (l)	50
Maximum pressure (bar)	10
Intake capacity (l/min)	352 L/min (5.867 L/s)
Free air delivery (l/min)	210 L/min (3.5 L/s)
Noise level dB (A) (0 m)	92
Voltage (V)	230 V / 50 Hz / 1 Ph
EAN 13	8712418438437
Manufacturer	Airpress Polska Sp. z o.o.

